



PECO Pallet: GMA 48x40 Block Pallet Specifications

Revised 12.10.2021

Features & Benefits:

Engineered Around Four Key Values: Quality, Service, Control and Safety

- ▶ Injecting highest quality standards into global supply chains
- ▶ Responsiveness beyond customer expectations

State-of-the-Art High-Tech Pallet Construction

- ▶ Performance that improves your bottom line
- ▶ A total of 26 boards and 138 fasteners per pallet
- ▶ Pallets can be heat-treated to comply with ISPM-15 phytosanitary standards (available at an extra charge; allow 5 days for delivery)

Lowest Total Lifecycle Cost per Pallet

- ▶ Each pallet rated at 2,800 lbs. [1,270.08kg] capacity
 - Edge-racked 40" [1,016mm] width; 34" [864mm] or 36" [914mm] span
 - Edge-racked 48" [1,219mm] width; 44" [1,118mm] span

Strategically Customized Transportation Solutions

- ▶ Solutions-focused sales and management team
- ▶ "Close to your door" service and support

▶ Top View



▶ Bottom View



▶ Side View



At **PECO Pallet**, we make sure that every pallet is constructed and maintained to the **highest quality standards** in the industry.

PECO Pallet: GMA 48x40 Block Pallet Specifications

Specifications:

▶ Pallet ID

PECO 48x40 Block Pallet (Decks w/ Clinch)

▶ Classification

48.00" x 40.00" x 5.56" [1,219mm x 1,016mm x 141mm], Block-Class, Double-Face, Non-Reversible, Full 4-Way, Multiple-Use, New Manufacture, 65-68 lbs. [29.484-30.8448 kg]

Each pallet rated at 2,800 lbs. [1,270.08 kg] capacity:

-Edge-racked 40" [1,016mm] width; 34" [864mm] or 36" [914mm] span

-Edge-racked 48" [1,219mm] width; 44" [1,118mm] span

Components:

▶ Top Deck

Style Type	Deckboard/Stringerboard New Lumber		
Number	Thickness	Width	Length
5	0.688" [17.48mm]	3.500" [89mm]	40.00" [1,016mm]
4	0.688" [17.48mm]	5.500" [140mm]	40.00" [1,016mm]

Mat Assembly Method, Mat Fasteners Clinched

Select Top Deck Leadboards

Volume: 7.5 bd ft [0.0177 cubic meter]

▶ Bottom Deck

Style Type	Perimeter Base New Lumber		
Number	Thickness	Width	Length
2	0.688" [17.48mm]	5.500" [140mm]	40.00" [1,016mm]
3	0.688" [17.48mm]	5.500" [140mm]	37.00" [940mm]

Volume: 5.0 bd ft [0.0118 cubic meter]

▶ Top Stringer Boards

Type	New Lumber		
Number	Thickness	Width	Length
3	0.688" [17.48mm]	5.500" [140mm]	48.00" [1,219mm]

Volume: 3.8 bd ft [0.0090 cubic meter]

▶ Blocks

Type Orientation	Lumber Sidegrain Nailing		
Number	Thickness	Width	Length
3	3.500" [89mm]	5.000" [127mm] or 5.500" [140mm]	3.75" [95.25mm]
6	3.500" [89mm]	5.000" [127mm] or 5.500" [140mm]	7.50" [190.50mm]

Volume: 6.9 bd ft [0.0163 cubic meter]

Materials:

▶ Fasteners:

Mat Fast	TD Blk Fast	BD Blk Fast
Fastener ID		
1.625" x 0.105" [41.28mm x 2.67mm]	3.00" x 0.135" RSB [76.20mm x 3.43mm]	2.25" x 0.120" RSB [57.15mm x 3.05mm]
Fastener Type		
Smooth Shank	Annular Ring	Annular Ring
Fastener Length		
1.63" [41.40mm]	3.00" [76.20mm]	2.25" [57.15mm]
Thread Length		
0	2.5" [63.5mm]	1.5" [38.10mm]
Thread Diameter		
0	0.141" [3.58mm]	0.126" [3.20mm]
Wire Diameter		
0.105" [2.67mm]	0.135" [3.76mm]	0.120" [3.12mm]
Head Diameter		
0.270" [6.86mm]	0.285" [7.24mm]	0.285" [7.24mm]
Rings		
0	32 rings/inch	32 rings/inch
MIBANT Angle		
60	25	32
Total Number		
36	45	57



All materials generated from the PDS software (PDS Materials), including without limitation specification sheets, drawings, analyses and all other output, are protected by copyright and other intellectual property laws. The direct pallet user customer may not copy the PDS materials without the express written permission of the PDS licensee that provided the customer with the PDS materials.